Ori-Plast



upvc swr drainage systems

Application

Ori-Plast uPVC SWR pipes are used for drainage & sewerage purposes. The Handling, Transportation, Installation and after sales service. Ori-Plast SWR range is ideal for both residential and commercial premises of any height due to its superiority as compared to conventional systems such as Cast Iron. Ori-Plast SWR pipes and fittings are now available with High Flow Rate throughout life due to its smooth internal surface. Prefit PP rubber ring which is leak proof and easy to install.



Benefits / Advantages

- Unaffected by chemicals and industrial waste.
- Prefit PP Ring provides sure leak proof joints.
- Corrosion resistant.
- All weather resistant, no effect of sunlight (UV).
- Aesthetic Superiority to CI and AC systems.
- Immune from rodent attacks.

Product range

USAGE-Soil, Waste, Rain and Drainage

JOINTING-Solvent Cement Joint & Rubber Ring (Prefit PP Ring)

SWR Pipes

Туре	Description	Size(mm)	Length(mtr)	Color
	Single Socketed & Double Socketed	75.90.110.160	0.6. 0.9. 1.2. 1.8. 3.0. 6.0	White & Grey
В	Single Socketed & Double Socketed	75,90,110,160	0.6, 0.9, 1.2, 1.8, 3.0, 6.0	White & Grey

SWR Fittings

Item Size - 75mm & 110mm

Slip Coupler, Short Bend 45°, Bend 87.5°, Door Bend 87.5°, Cleaning Pipe, Bend 87.5°, Door Bend 87.5° (Right & Left), Single 'T' & Single 'T' with Door Single 'Y', Single 'Y' with Door, Double 'Y', Double 'Y' with Door, Single 'T', (Right & Left). Single 'T' with Door, Double 'T' & Double 'T' with Door, Vent Cowl, Pipe Clip, Socket Plug, Door Cap, Rubber Seal for Door, Nahani Trap with Jali, Ring Seal Adapter, Threading Bush Cap, Nahani Body, Nahani Pipe, Nahani Jali, Rubber Ring, Nahani Trap without Jali. Trap Body, 110 x 75mm, Reducer.

Nahani Trap without Jali.

Other Fittings

125mm Trap Body, Ptrap, QTrap & STrap (125 x 100mm), PTrap, QTrap & Multi Floor Trap, Multi Floor Trap with 3 X 50mm End Cap. Rubber Ring, S Trap (110 & 110mm), Rubber Lubricant 500gm & 1 kg, 110 mm Multi Floor Trap bore & Trap Insert Plate, 50mm Block (for Multi Trap), Reducer 110mm X 75mm.

For better understanding please refer to our price list.



ISO 9001: 2000 COMPANY



Registered Office

40, Strand Road, 3rd Floor Room No.9 Kolkata - 700 001 Phone: +91-33-2243 3396/97 Fax: +91-33-2243 2395 Email: contactus@oriplast.com customercare@oriplast.com

Delhi Branch Office

Unit No. 1402, R G Trade Tower B7, Netaji Subhash Place Wazirpur District Center Pitampura, New Delhi - 110 034 Ph: +91-11-2735 2164/65 Tele Fax: +91-11-4370 2640 Email: northsales@oriplast.com

C & F Agent, Cuttack M/s. Aditya Logistic

202/C, P.O.: Naya Bazar P.S.: Chauliaganj Cuttack - 753 004, Odisha Ph: +91-671-244 0419, 320 2318 Email: cuttackdepot@oriplast.com

Jaipur Branch Office

Plot No. K53, Flat No. G3 Kishan Nagar (Shyam Nagar) Jaipur - 302 019 (Rajasthan)

Corporate Office

9A, Wood Street, Kolkata - 700 016 Phone: +91-33-2283 9054/58 Fax: +91-33-2283 9059 E-mail: corporate@oriplast.com sales@oriplast.com

Hyderabad Branch Office

Flat No. 6A, 6th Floor, Amrutha Estate Dhruvatara Apartment, somajiguda Hyderabad - 500 082 (A.P.) Ph: +91-40-6598 3033 Fax: +91-40-2337 5618 Email: hyderabad@oriplast.com

Bhubaneshwar Branch Office

Plot No. 275 Hotel Mayfair Road Ground Floor, Jaydev Vihar, P.O. RRL Bhubaneswar - 751 013 Odisha Tele Fax: +91-674-236 1336

Guwahati Branch Office

Suhagpur, Promothes Baruah Road House no. 12, Rehabari, Guwahati - 781008, Assam Tele Fax: +91-141-229 7111 Ph.: 09864780080 / 9207080080

Balasore Works

O.T. Road, P.O. & Dist. - Balasore, Odisha - 756 001 Ph.: +91-6782-26 4551-53, Fax: +91-6782-26 2551, Email: works@oriplast.com

Toll Free No: 1800 123 2123



cPVC, uPVC, PVC, SWR, HDPE Pipes & Fittings, Water Tanks for Domestic, Agricultural & Industrial usage











Toll Free No: 1800 123 2123 sales@oriplast.com, www.oriplast.com